Model Specifications

Canrig Titan™



Weight and Dimensional Data

Retracted Dimensions (LxWxH)	102 × 52 × 98 in.	2,591 × 1,321 × 2,489 mm
Extended Dimensions (LxWxH)	156 × 52 × 127 in.	3,962 × 1,321 × 3,226 mm
Shipping Dimensions (LxWxH)	102 × 72 ½ x 118 in.	2,591 × 1,842 × 2,997 mm
Weight (Installed)	10,500 lbs.	4,763 kg
Weight (Shipping)	11,500 lbs.	5,216 kg

Technical Specifications

Tool Joint Diameter Range	3 ½ in. – 9 ½ in.	89 mm – 241 mm
Minimum Hydraulic Requirements	3,000 psi @ 45 GPM*	*65 GPM Recommended
Makeup Torque (Max)	110,000 ft-lb	149,140 Nm
Breakout Torque (Max)	110,000 ft-lb	149,140 Nm
Spinner Torque with 5” DP @ 3,000 psi	3,000 ft-lb	4,067 Nm
Spinner Speed with 5” DP @ 55 GPM	106 RPM	
Horizontal Operational Range	95 in. – 110 in.	2,413 mm – 2,794 mm
Vertical Operational Range at 95” extension	26 ½ in. – 56 ½ in.	673 mm – 1,435 mm
Vertical Operational Range at 110” extension	34 ¾ in. – 64 ¾ in.	883 mm – 1,645 mm
Rotation	359°	

© Nabors Industries Ltd. 2026 - All Rights Reserved.